

#### Material Name:

Safety Data

Fire-Retardant Faced, Formaldehyde-free Fiber Glass Building Insulation

Sheet ID: 1021

# Section 1 - Product and Company Identification

# Hazard Label WARNING Company Information

Johns Manville Insulation Systems P.O. Box 5108 Denver, CO 80127 USA Telephone: 303-978-2000 8:00AM-5:00PM M-F

Internet Address: http://www.jm.com

Emergency: 800-424-9300 (Chemtrec, In English)

#### **Trade Names:**

Basement Wall Insulation, Faced Condensation Blanket, Faced FSK-25 Faced Batts ITP Concrete Wall Insulation® Laminated Metal Building Insulation

Panel-Deck FSK-25 Panel-Deck PSK PSK-Faced Roll

Use: For use in commercial, residential, manufactured housing, and metal buildings.

## Section 2 - Hazards Identification

## **Emergency Overview**

Inhalation of excessive amounts of dust from the product may cause temporary upper respiratory irritation and/or congestion-remove individual to fresh air.

#### Inhalation

Irritation of the upper respiratory tract (scratchy throat), coughing, and congestion may occur in extreme exposures.

#### Skin

Temporary irritation (itching) or redness may occur.

#### Ingestion

This product is not intended to be ingested (eaten). If ingested, it may cause temporary irritation to the gastrointestinal (digestive) tract.

### Eyes

Temporary irritation (itching) or redness may occur.

#### Ears

Temporary irritation (itching) or redness may occur.

## Primary Routes of Entry (Exposure)

Inhalation, skin, and eye contact.

#### **Target Organs**

Nose (nasal passages), throat, lungs, skin, eyes

#### Medical Conditions Aggravated by Exposure

Pre-existing chronic respiratory, skin, or eye diseases or conditions.

# Section 3 - Composition/Information on Ingredients

| CAS # Component |  | Percent |  |
|-----------------|--|---------|--|
| Not Available   | Fiber glass wool   | 80-98   |  |
| Not Available   | Thermoset resin  | 2-15    |  |
| Not Available   | Foil/kraft, FSK, polyethylene, PSK, and various metal building facings | 0-15    |  |
| 1309-64-4       | Antimony trioxide (may be in facing or adhesive)                       | >0.1    |  |

## Component Information

Antimony trioxide (fire retardant) may be present in the facings and/or adhesives. Occupational exposure to airborne antimony trioxide is not expected to occur due to product form(s) and intended use(s). Exposure limit is given for reference only.

## General Product Description

Fibrous glass board, batt, blanket, with various facings. No significant odor.

## Section 4 - First Aid Measures

#### First Aid: Inhalation

If dust is inhaled in excess of exposure limits referenced in section 8 of this safety data sheet, remove individual to fresh air. Drink water to clear throat, and blow nose to remove dust. A saline spray in the nose may help clear any fibers.

 Material Name: Fiber Glass Building Insulation, Formaldehyde-free

Safety Data Sheet

ID: 1021

First Aid: Skin

Wash gently with soap and water to remove dust and fibers. Alternatively, fibers can be removed from the skin by use of ordinary masking or wrapping tape. Should irritation persist, seek medical attention.

First Aid: Ingestion

Rinse mouth with water to remove dust and fibers and drink plenty of water to help reduce irritation. If irritation persists, seek medical attention.

First Aid: Eyes

Do not rub or scratch eyes. Dust particles may cause the eye to be scratched. Flush eyes with large amounts of water until irritation subsides. If irritation persists, seek medical attention.

First Aid: Ears

Wash exposed skin with soap and water. If irritation develops in the inner ear, seek medical attention.

First Aid: Notes to Physician

Dust from the product may cause mechanical irritation of the eyes, skin, and upper respiratory tract. Treat symptomatically.

Method Used: Not applicable

Lower Flammable Limit (LFL): Not applicable

Flammability Classification: Not determined

## Section 5 - Fire Fighting Measures

Flash Point: Not applicable

Upper Flammable Limit (UFL): Not applicable Auto Ignition: Not determined

Rate of Burning: Not determined

**General Fire Hazards** 

There is no potential for spontaneous fire or explosion. Inorganic glass fibers are naturally non-combustible and non-flammable.

Extinguishing Media

Carbon dioxide (CO<sub>2</sub>), water, water fog, dry chemical.

Fire Fighting Equipment/Instructions

No special procedures are expected to be necessary for this product. Normal fire fighting procedures should be followed to avoid inhalation of smoke and gases.

## Section 6 - Accidental Release Measures

## Clean-Up Procedures

Pick up large pieces. Vacuum dusts. If sweeping is necessary, use a dust suppressant such as water. Do not dry sweep dust accumulation. These procedures will help to minimize potential exposures.

## Section 7 - Handling and Storage

## **Handling Procedures**

Use protective equipment as described in Section 8 of this safety data sheet when handling uncontained material. Handle in accordance with good industrial hygiene and safety practices.

## **Storage Procedures**

Warehouse storage should be in accordance with package directions, if any. Material should be kept clean, dry, and in original packaging.

## Section 8 - Exposure Controls / Personal Protection

### **Exposure Guidelines**

## A: General Product Information

The Occupational Safety and Health Administration (OSHA) has not adopted specific occupational exposure standards for fiber glass. Fiber glass is treated as a nuisance dust and is regulated by OSHA as a particulate not otherwise regulated (total dust) shown in CFR 1910.1000 Table Z-3.

Respirable fraction 5 mg/m3

Total dust 15 mg/m3

JM has adopted the fiber glass industry voluntary Product Stewardship Program (PSP), formerly the NAIMA-OSHA Health and Safety Partnership Program (HSPP). Under the PSP, JM recommends that exposures be limited to the voluntary concentration of 1 f/cc TWA for fibers longer than 5 microns with a diameter less than 3 microns. This will help minimize potential irritation effects. The PSP also includes the PPE recommendations described below.

Page 2 of 6

Issue Date: 01/03/2013 Revision: 1.0015

Material Name: Fiber Glass Building Insulation, Formaldehyde-free

Safety Data Sheet

ID: 1021

#### **B: Component Exposure Limits**

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

ACGIH: 0.5 mg/m3 TWA (related to Antimony) OSHA: 0.5 mg/m3 TWA (related to Antimony)

#### PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Safety glasses with side shields are recommended to keep dust out of the eyes.

**Personal Protective Equipment: Ears** 

Use ear protection (earplugs, hood, or earmuffs) to prevent airborne dust or fibers from entering the ear, if necessary.

Personal Protective Equipment: Skin

Leather or cotton gloves should be worn to protect against mechanical abrasion. See also Personal Protective Equipment: General, below.

Personal Protective Equipment: Respiratory

A NIOSH-certified respirator should be used if ventilation is unavailable, or is inadequate for keeping dust and fiber levels below the applicable exposure limits referenced in Section 8 of this SDS.

Ventilation

In fixed manufacturing settings, local exhaust ventilation should be provided at areas of cutting to remove airborne dust and fibers. General dilution ventilation should be provided as necessary to keep airborne dust and fibers below the applicable exposure limits and guidelines. The need for ventilation systems should be evaluated by a professional industrial hygienist.

Personal Protective Equipment: General

Wear a cap, a loose-fitting, long-sleeved shirt and long pants to protect skin from irritation. Exposed skin areas should be washed with soap and water after handling or working with fiber glass. Clothing should be washed separately from other clothes, and the washer should be rinsed thoroughly (run empty for a complete wash cycle). This will reduce the chances of fiber glass being transferred to other clothing.

# **Section 9 - Physical & Chemical Properties**

Appearance: Fibrous glass board, batt, blanket, or with Odor: No significant odor

various facings

Physical State: Solid Not applicable pH: Vapor Pressure: Not applicable Vapor Density: Not applicable **Boiling Point:** Not applicable **Melting Point:** >704°C/1300°F Solubility (H<sub>2</sub>O): Nil Specific Gravity: Variable Freezing Point: Not applicable **Evaporation Rate:** Not applicable

Freezing Point: Not applicable Evaporation Rate: Not applicable

Percent Volatile: 0 VOC: Not determined

## Section 10 - Stability & Reactivity Information

#### Stability

These products are not reactive.

## **Hazardous Decomposition**

May form carbon dioxide and carbon monoxide.

## **Hazardous Polymerization**

Will not occur.

# Section 11 - Toxicological Information

## **Acute Toxicity**

#### A: General Product Information

Dust from this product is a mechanical irritant, which means that it may cause temporary irritation or scratchiness of the throat, and/or itching of the eyes and skin.

## B: Component Analysis - LD50/LC50

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

Oral LD50 Rat: >34600 mg/kg

Material Name: Fiber Glass Building Insulation, Formaldehyde-free

**Safety Data Sheet** 

ID: 1021

## **Component Carcinogenicity**

#### Fiber glass wool

NTP: Not listed.

IARC: Group 3 - Not Classifiable (IARC Monograph 81 [2002] (listed under Man-made mineral fibres),

Monograph 43 [1988])

#### Antimony trioxide (may be in facing or adhesive) (1309-64-4)

ACGIH: A2 - Suspected Human Carcinogen (production)

IARC: Group 2B - Possibly Carcinogenic to Humans (IARC Monograph 47 [1989])

## **Chronic Toxicity**

#### Fiber Glass Wool (non-durable glass fibers):

In October 2001, IARC classified fiber glass wool as Group 3, "not classifiable as to its carcinogenicity to humans." The 2001 decision was based on current human and animal research that shows no association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease

In 2011, the National Toxicology Program (NTP, a component of the United States Department of Health and Human Services) issued its 12th Report on Carcinogens (Report). The Report makes clear that any glass fibers that have been successfully assessed in an animal study and shown no cancer hazard are NOT among those "certain" fibers and NOT listed in the Report.

The glass fibers comprising the products on this MSDS have either been successfully assessed by appropriate animal protocols and / or have modeled Kdis values such that they are considered non-durable and the current human and animal research that shows no association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease is applicable to these fibers.

# **Section 12 - Ecological Information**

## Ecotoxicity

#### A: General Product Information

No data available for this product.

#### **B: Component Analysis - Ecotoxicity - Aquatic Toxicity**

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

96 Hr LC50 Pimephales promelas: 833.0 mg/L; 96 Hr LC50 Lepomis macrochirus: 530 mg/L; 96 Hr LC50 Brachydanio rerio: >1000 mg/L [static]

72 Hr EC50 Selenastrum capricornutum: 67 mg/L

7 Hr EC50 Pseudomonas putida: >3.5 mg/L

48 Hr EC50 Daphnia magna: >1000 mg/L

# **Section 13 - Disposal Considerations**

## **US EPA Waste Number & Descriptions**

#### A: General Product Information

This product is not expected to be a hazardous waste when it is disposed of according to the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Product characterization after use is recommended to ensure proper disposal under federal and/or state requirements.

## **B: Component Waste Numbers**

No EPA Waste Numbers are applicable for this product's components.

#### **Disposal Instructions**

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

## Section 14 - Transport Information

#### **International Transport Regulations**

These products are not classified as dangerous goods according to international transport regulations.

# **Section 15 - Regulatory Information**

## **US Federal Regulations**

## A: General Product Information

SARA 311/312: This product is not classified as hazardous under SARA 311/312.

| Page 4 of 6 | Issue Date: | 01/03/2013 Revision: 1.00 | 15 |
|-------------|-------------|---------------------------|----|

ID: 1021

#### **B: Component Analysis**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

CERCLA: 1000 lb final RQ; 454 kg final RQ

#### State Regulations

#### A: General Product Information

The glass fibers in this product are not known to be regulated.

Other state regulations may apply. Check individual state requirements.

## **B: Component Analysis - State**

The following components appear on one or more of the following state hazardous substances lists:

| Component  | CAS#      | CA  | FL | MA  | MN  | NJ  | PA  |
|--|-----------|-----|----|-----|-----|-----|-----|
| Antimony trioxide (may be in facing or adhesive) | 1309-64-4 | Yes | No | Yes | Yes | Yes | Yes |

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the state of California to cause cancer.

| e. The product contains a chemical known to the state of camerna to cause cancer. |               |  |
|---|---------------|--|
| Component   | CAS#          |  |
| Fiber glass wool  | Not Available |  |
| Antimony trioxide (may be in facing or adhesive)                                  | 1309-64-4     |  |

#### **TSCA Status**

This product and its components are listed on the TSCA 8(b) inventory.

None of the components listed in this product are listed on the TSCA Export Notification 12(b) list.

## International Regulations

## A: General Product Information

These products are considered articles under both U.S. and international product regulations and as such, these products do not require registration or notification on the various country-specific inventories.

#### B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

| Component        | CAS#          | Minimum Concentration          |
|------------------|---------------|--------------------------------|
| Fiber glass wool | Not Available | 1 % (related to Fibrous glass) |

### **WHMIS Classification**

Controlled Product Classification: D2A

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations. This SDS contains all the information required by the Controlled Products Regulations.


## **Section 16 - Other Information**

#### Other Information

Prepared for: Johns Manville Insulation Systems P. O. Box 5108 Denver, CO USA 80217-5108

Prepared by: Johns Manville Technical Center P.O. Box 625005 Littleton, CO USA 80162-5005

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.



| Date     | MSDS#       | Reason   |
|----------|-------------|--|
| 03/11/02 | 1021-1.0000 | New Products.  |
| 06/14/02 | 1021-1.0001 | Sect. 1 Trade Names: Added trade names (total of 21).  |
| 11/18/02 | 1021-1.0002 | Sect. 1: RID changed to BID. Added 5 trade names. Sect. 11 updated FGW to IARC Grp. 3.   |
| 02/12/03 | 1021-1.0003 | Sect. 1, trade names: added "Formaldehyde-free" to trade names that are also sold with UPF binder (see MSDS 1010).   |
| 06/30/03 | 1021-1.0004 | Sect. 10 Correction: remove hydrogen cyanide as possible product of burning of insulation binder.  |
| 10/27/03 | 1021.1.0005 | Section 1 added Kraft-Faced MR Insulation.   |
| 11/26/03 | 1021-1.0006 | Section 16 division change from RID to BID   |
| 02/13/04 | 1021-1.0007 | Section 3 added 'blue kraft' to appearance. Regulatory update. Minor edits.  |
| 03/23/05 | 1021-1.0008 | Sect. 1, trade name removals: Best-Pak; ComfortTherm; Commercial BI, Formaldehyde-free; DuctWrap Roll; EasyFit; FGBI, Formaldehyde-free; Foil Faced Batts; High Density Blowing Wool; Kraft Faced Batts; Kraft Faced MR Insulation; Microlite L; Micro-Pak; Mobinsul; Multi-Purpose Insulation; Pan Insul; Rich R Blowing Wool; Thermal/Accoustical Batts and Rolls; UMBI; Unfaced Sound Control Batts; RBI, Formaldehyde-free; PEBS Blanket; & High Performance Batts. Basement Wall Insulation was changed to Basement Wall Insulation, Faced. Panel-Deck was changed to Panel-Deck FSK-25 and Panel-Deck PSK. |
| 04/05/05 | 1021-1.0009 | Sect. 1 addition of Insul-SHIELD, Faced Boards. Sect. 2 addition of carbon black.  |
| 06/24/05 | 1021-1.0010 | Sect. 2 minor edit to composition  |
| 03/10/08 | 1021-1.0011 | Removed Insul-SHIELD®, Faced Boards from trade names. SDS updated to GHS format.   |
| 11/23/09 | 1021-1.0012 | Addition of Hi-Lo Temp® Formaldehyde Free Fiber Glass Insulation   |
| 12/31/12 | 1021-1.0013 | Inserts to trade names.  |
|          | 1021-1.0014 | Updated regulatory information in section 11.  |
| 01/03/13 | 1021-1.0015 | Update trade names.  |

End of Sheet 1021