



We create chemistry

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21

Version: 5.0

Page: 1/10

(50256424/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

WALLTITE* ECO v.3 F RESIN

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component; industrial chemicals

Suitable for use in industrial sector: Polymers industry; chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666

BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: resin

Synonyms: Urethane System Resin Component

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
STOT RE	2 (oral)	Specific target organ toxicity — repeated exposure

Label elements

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21
Version: 5.0

Page: 2/10
(50256424/SDS_GEN_CA/EN)

Pictogram:



Signal Word:
Warning

Hazard Statement:

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure (oral).

Precautionary Statements (Prevention):

P280 Wear protective gloves and eye/face protection.
P260 Do not breathe dust/gas/mist/vapours.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/attention if you feel unwell.
P303 + P362 IF ON SKIN (or hair): Wash with plenty of soap and water.
P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
P362 + P364 Take off contaminated clothing and wash before reuse.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

According to Controlled Products Regulations (CPR) (SOR/88-66)

Emergency overview

Irritating to eyes, respiratory system and skin.
May be harmful if swallowed.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
31568-06-6	>= 20.0 - < 25.0 %	Ethanol, 2-((2-aminoethyl)amino)-, polymer with methyloxirane
13674-84-5	>= 10.0 - < 20.0 %	tris(2-chloro-1-methylethyl)phosphate
140-07-8	>= 1.0 - < 3.0 %	Ethanol, 2,2',2'',2'''-(1,2-ethanediylidinitrilo)tetrakis-
111-46-6	>= 0.3 - < 3.0 %	diethylene glycol
280-57-9	>= 0.3 - < 1.0 %	triethylenediamine

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21
Version: 5.0

Page: 3/10
(50256424/SDS_GEN_CA/EN)

406-58-6	>= 10.0 - < 15.0 %	Butane, 1,1,1,3,3-pentafluoro-
431-89-0	>= 1.0 - < 3.0 %	1,1,1,2,3,3,3-Heptafluoropropane
460-73-1	>= 5.0 - < 7.0 %	Propane, 1,1,1,3,3-pentafluoro-

According to Controlled Products Regulations (CPR) (SOR/88-66)

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
111-46-6	>= 1.0 - <= 5.0 %	diethylene glycol
406-58-6	>= 10.0 - <= 15.0 %	Butane, 1,1,1,3,3-pentafluoro-
431-89-0	>= 1.0 - <= 5.0 %	1,1,1,2,3,3,3-Heptafluoropropane
460-73-1	>= 3.0 - <= 7.0 %	Propane, 1,1,1,3,3-pentafluoro-

The product contains:

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
56-81-5	>= 1.0 - < 3.0 %	glycerol
25265-71-8	>= 1.0 - < 3.0 %	dipropylene glycol

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Wash thoroughly with soap and water.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Information on: tris(2-chloro-1-methylethyl)phosphate

Symptoms: Overexposure may cause: convulsions, depression, hypoxemia, tremors

Information on: diethylene glycol

Symptoms: Overexposure may cause: vomiting, coma, abdominal cramps, lethargy, nausea, diarrhea, headache

Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21

Page: 4/10

Version: 5.0

(50256424/SDS_GEN_CA/EN)

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, carbon dioxide, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture.

Protection against fire and explosion:

No explosion proofing necessary.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids. Segregate from oxidants.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Further information on storage conditions: No special precautions necessary. Avoid extreme heat. Store protected against freezing.

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21
Version: 5.0

Page: 5/10
(50256424/SDS_GEN_CAVEN)

Storage stability:
Storage temperature: 60 - 80 °F
Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

glycerol	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
----------	----------	-------------------------------------------------------------------------------------------------------------------------------------

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	mild, solvent-like	
Odour threshold:		No applicable information available.
Colour:	Purple	
pH value:	>= 7	
Freezing point:		No applicable information available.
Sublimation point:		No applicable information available.
Flash point:	> 93.3 °C	
Flammability:	not flammable	
Lower explosion limit:		For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.
Upper explosion limit:		For liquids not relevant for classification and labelling.
Autoignition:	> 250 °C	
Density:	1.2 g/cm3	(20 °C)
Relative density:		No applicable information available.

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21
Version: 5.0

Page: 6/10
(50256424/SDS_GEN_CA/EN)

Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Self-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	partly soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Temperature: < 0 degrees Celsius

Incompatible materials

acids, oxidizing agents, isocyanates

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21
Version: 5.0

Page: 7/10
(50256424/SDS_GEN_CA/EN)

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of low toxicity after single ingestion.

Oral

Type of value: ATE
Value: 4,200 mg/kg

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Origin of data: expert judgement

Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Teratogenicity

Assessment of teratogenicity: Contains a suspect teratogen.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21
Version: 5.0

Page: 8/10
(50256424/SDS_GEN_CA/EN)

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Medical conditions aggravated by overexposure

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

The product has not been tested. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21
Version: 5.0

Page: 9/10
(50256424/SDS_GEN_CA/EN)

Container disposal:

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

14. Transport Information

Land transport TDG

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released; restriction on use / listed

This product contains a substance subject to a Significant New Activity (SNAc) as disclosed in the Canada Gazette.

SNAc 13957, CGII, Vol143No21p1974, CGII, Vol140No24p1953

WHMIS

classification:

D1B: Materials Causing Immediate and Serious
Toxic Effects - Toxic material



THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2015/04/21

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in

Safety Data Sheet

WALLTITE® ECO v.3 F RESIN

Revision date : 2015/04/21

Page: 10/10

Version: 5.0

(50256424/SDS_GEN_CA/EN)

a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

WALLTITE is a registered trademark of BASF Canada or BASF SE
END OF DATA SHEET